UMW AO4413

-30V P-Channel MOSFET

1.Description

The AO4413 provide excellent $R_{DS(ON)}$, and ultra-low low gate charge with a 25V gate rating. This device is suitable for use as a load switch or in PWM appli-cations.

2.Features

- V_{DS}=-30V
- I_D =-15A
- $R_{DS(ON)}$ <7mΩ(V_{GS}=-10V)
- $R_{DS(ON)}$ <8.5mΩ(V_{GS}=-4.5V)
- RoHS and Halogen-Free Compliant

3.Pinning information

Pin	Symbol	Description
4	G	GATE
1,2,3	S	SOURCE
5,6,7,8	D	DRAIN

SOP-8





4.Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current	T_A=25°C	I_D	-15	A
	T_A=70°C		-12.8	
Pulsed Drain Current [C]		I_{DM}	-120	
Avalanche Current [C]		I_{AS},I_{AR}	50	A
Avalanche energy L=0.1mH [C]		E_{AS},E_{AR}	125	mJ
Power Dissipation [B]	T_A=25°C	P_D	3.1	W
	T_A=70°C		2	
Junction and Storage Temperature Range		T_J,T_{STG}	-55 to 150	°C

5.Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	31	40	°C/W
Maximum Junction-to-Ambient [A D]	Steady-State		59	75	°C/W
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	16	24	°C/W

6.Electrical Characteristic (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	BV_{DSS}	I_D=-250μA, V_{GS}=0V	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-30V, V_{GS}=0V			-1	μA
		T_J=55°C			-5	
Gate-Body leakage current	I_{GSS}	V_{DS}=0V, V_{GS}=±25V			±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250μA	-1.5	-2.5	-3.5	V
On state drain current	$I_{D(ON)}$	V_{GS}=-10V, V_{DS}=-5V	-120			A
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}=-20V, I_D=-15A		5.3	7	mΩ
		V_{GS}=-10V, I_D=-15A		6.4	8.5	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V, I_D=-15A		35		S
Diode Forward Voltage	V_{SD}	I_S=-1A, V_{GS}=0V		-0.7	-1	V
Maximum Body-Diode Continuous Current	I_S				-4	A
Input Capacitance	C_{iss}	V_{GS}=0V, V_{DS}=-15V, f=1MHz	2310	2890	3500	pF
Output Capacitance	C_{oss}		410	585	760	pF
Reverse Transfer Capacitance	C_{rss}		280	470	660	pF
Gate resistance	R_g	V_{GS}=0V, V_{DS}=0V, f=1MHz	1.9	3.8	5.7	Ω
Total Gate Charge	Q_g	V_{GS}=-10V, V_{DS}=-15V, I_D=-15A	40	51	61	nC
Gate Source Charge	Q_{gs}		10	12	14	nC
Gate Drain Charge	Q_{gd}		10	16	22	nC
Turn-On DelayTime	$t_{D(on)}$	V_{GS}=-10V, V_{DS}=-15V, R_L=1Ω,R_{GEN}=3Ω		16		ns
Turn-On Rise Time	t_r			12		ns
Turn-Off DelayTime	$t_{D(off)}$			45		ns
Turn-Off Fall Time	t_f			22		ns
Body Diode Reverse Recovery Time	t_{rr}	I_F=-15A, dI/dt=100A/μs	14	18	22	ns
Body Diode Reverse Recovery Charge	Q_{rr}	I_F=-15A, dI/dt=100A/μs	9	11	13	nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The value in any given application depends on the user's specific board design.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150°C, using ≤ 10s junction-to-ambient thermal resistance.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C. Ratings are based on low frequency and duty cycles to keep initial T_J=25°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-ambient thermal impedence which is measured with the device mounted on $1in^2$ FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(MAX)}$=150°C. The SOA curve provides a single pulse rating.

7.1Typical characteristic



Fig 1: On-Region Characteristics (Note E)



Figure 2: Transfer Characteristics (Note E)



Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)



Figure 4: On-Resistance vs. Junction Temperature (Note E)



Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)



Figure 6: Body-Diode Characteristics(Note E)

7.2Typical characteristic



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Single Pulse Avalanche capability (Note C)



Figure 10: Maximum Forward Biased Safe Operating Area (Note F)



Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)

7.3Typical characteristic



Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)

8.SOP-8 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	c	D	E	E1	e	h	L
Min	-	0.05	1.30	0.60	0.39	0.20	4.70	5.80	3.80	1.24	0.30	0.50
Max	1.75	0.20	1.50	0.70	0.47	0.24	5.10	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°

9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW AO4413	SOP-8	3000	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.