UMW AOD417

-30V P-Channel MOSFET

1.Description

The AOD417 uses advanced technology to provide excellent $R_{DS(ON)}$, low gate charge and low gate resistance. ellent thermal resistance of the DPAK package, this device is well suited for high current load applications.

2.Features

- $V_{DS\ (V)}$=-30V
- I_D=-25A(V_{GS}=-10V)
- $R_{DS(ON)}$<25mΩ(V_{GS}=-10V)
- $R_{DS(ON)}$<30mΩ(V_{GS}=-4.5V)
- RoHS Compliant
- Halogen Free*

3.Pinning information

Pin	Symbol	Description
1	G	GATE
3	S	SOURCE
2	D	DRAIN

TO-252(DPAK)
top view





4.Absolute Maximum Ratings T_A= 25°C

Parameter		Symbol	Rating	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current [B,G]	T_A=25°C [G]	I_D	-25	A
	T_A=100°C		-20	
Pulsed Drain Current [c]		I_{DM}	-60	
Avalanche Current [c]		I_{AR}	-14	
Repetitive avalanche energy L=0.3mH [c]		E_{AR}	30	mJ
Power Dissipation [B]	T_C=25°C	P_D	50	W
	T_C=100°C		25	
Power Dissipation [A]	T_A=25°C	P_{DSM}	2.5	
	T_A=70°C		1.6	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 175	°C

5.Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	16.7	25	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		40	50	°C/W
Maximum Junction-to-Case [D]	Steady-State	$R_{\theta JC}$	2.5	3	°C/W

6.Electrical Characteristic (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	BV_{DSS}	I_D=-250μA, V_{GS}=0V	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-24V, V_{GS}=0V			-1	μA
		T_J=55°C			-5	μA
Gate-Body leakage current	I_{GSS}	V_{DS}=0V, V_{GS}=±20V			±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250μA	-1	-1.9	-3	V
On state drain current	$I_{D(ON)}$	V_{GS}=-10V, V_{DS}=-5V	-60			A
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-20A		28	35	mΩ
		V_{GS}=-4.5V, I_D=-7A		30	55	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V, I_D=-20A		18		S
Diode Forward Voltage	V_{SD}	I_S=-1A, V_{GS}=0V		-0.75	-1	V
Maximum Body-Diode Continuous Current	I_S				-6	A
Input Capacitance	C_{iss}	V_{GS}=0V, V_{DS}=-15V, f=1MHz		920		pF
Output Capacitance	C_{oss}			140		pF
Reverse Transfer Capacitance	C_{rss}			90		pF
Gate resistance	R_g	V_{GS}=0V, V_{DS}=0V, f=1MHz		6	9	Ω
Total Gate Charge (10V)	Q_g(10V)	V_{GS}=-10V, V_{DS}=-15V, I_D=-20A		16.2		nC
Total Gate Charge (4.5V)	Q_g(4.5V)			8.2		nC
Gate Source Charge	Q_{gs}			2.9		nC
Gate Drain Charge	Q_{gd}			3.6		nC
Turn-On DelayTime	$t_{D(on)}$	V_{GS}=-10V, V_{DS}=-15V, R_L=0.75Ω, R_{GEN}=0.75Ω		8		ns
Turn-On Rise Time	t_r			30		ns
Turn-Off DelayTime	$t_{D(off)}$			22		ns
Turn-Off Fall Time	t_f			26		ns
Body Diode Reverse Recovery Time	t_{rr}	I_F=-20A, dI/dt=100A/μs		23		ns
Body Diode Reverse Recovery Charge	Q_{rr}	I_F=-20A, dI/dt=100A/μs		14		nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The Power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design, and the maximum temperature of 175°C may be used if the PCB allows it.

B. The power dissipation P_D is based on $T_{J(MAX)}$=175°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=175°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedence which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=175°C.

G. The maximum current rating is limited by bond-wires.

H. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C.The SOA curve provides a single pulse rating.

7.1Typical characteristic



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

7.2Typical characteristic



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note F)



Figure 10: Single Pulse Power Rating Junction-to Case (Note F)



Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

7.3Typical characteristic



Figure 12: Single Pulse Avalanche capability



Figure 13: Power De-rating (Note B)



Figure 14: Current De-rating (Note B)



Figure 15: Single Pulse Power Rating Junction-to Ambient (Note H)



Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)

8.TO-252 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A1	A2	A3	b	c	D	D1	D2	E	E1	E2	e	L1	L2	L3	θ
Min	0.00	2.18	0.90	0.65	0.46	6.35	4.95	4.32	9.40	5.97	5.21	2.286	0.89	1.70	0.60	0.00
Max	0.13	2.39	1.10	0.85	0.61	6.73	5.46	4.90	10.41	6.22	5.38	BSC	1.27	1.90	1.00	8.00

9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW AOD417	TO-252	2500	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.