UMW FDP8D5N10C

100V N-Channel MOSFET

1.Description

This N-Channel MV MOSFET is produced using process that has been optimized to minimize on-state resistance and yet maintain superior switching performance with best in class soft body diode.

2.1Features

- $V_{DS\ (V)}$=100V
- I_D=76A
- $R_{DS(ON)}$<8.5mΩ(V_{GS}=10V)

2.2Features

- Low Gate Charge
- Fast Switching
- Improved dv/dt Capability
- RoHS Compliant

3.Pinning information

Pin	Symbol	Description
1	G	GATE
2	D	SOURCE
3	S	DRAIN





4.Absolute Maximum Ratings T_C= 25°C

Parameter			Symbol	Rating	Units
Drain to Source Voltage			V_{DS}	100	V
Gate to Source Voltage			V_{GS}	±20	V
Drain Current - Continuous	T_C=25°C	(Note 3)	I_D	76	A
- Continuous	T_C=100°C	(Note 3)		54	A
- Pulsed		(Note 1)		304	A
Single Pulse Avalanche Energy		(Note 2)	E_{AS}	181	mJ
Power Dissipation	T_C=25°C		P_D	107	W
Power Dissipation	T_A=25°C			2.4	W
Storage Temperature Range			T_J, T_{STG}	-55 to 175	°C

* Drain current limited by maximum junction temperature.

5.Thermal Characteristics

Parameter	Symbol	Rating	Units
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.4	°C/W
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	62.5	°C/W

6.Electrical Characteristic (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain to Source Breakdown Voltage	BV_{DSS}	I_D=250μA, V_{GS}=0V	100			V
Breakdown Voltage Temperature Coefficient	$\frac{\Delta BV_{DSS}}{\Delta T_J}$	I_D=250μA Referenced to 25°C		57		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=80V, V_{GS}=0V			1	μA
		V_{DS}=80V, T_J=150°C			500	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS}=±20V, V_{DS}=0V			±100	nA
Gate to Source Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=130μA	2	3	4	V
Static Drain to Source On Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=76A		7.4	8.5	mΩ
Forward Transconductance	g_{FS}	V_{DS}=5V, I_D=76A		68		S
Input Capacitance	C_{iss}	V_{DS}=50V, V_{GS}=0V, f=1MHz		1765	2475	pF
Output Capacitance	C_{oss}			1010	1415	pF
Reverse Transfer Capacitance	C_{rss}			16	25	pF
Gate Resistance	R_g		0.1	0.8	1.6	Ω
Turn-On Delay Time	$t_{D(on)}$	V_{DD}=50V, I_D=76A V_{GS}=10V,R_{GEN}=6Ω		12	22	ns
Rise Time	t_r			11	20	ns
Turn-Off Delay Time	$t_{D(off)}$			18	28	ns
Fall Time	t_f			4	10	ns
Total Gate Charge	Q_g	V_{GS}=0V to 10 V, V_{DD}=50V, I_D=76A		25	34	nC
Gate to Source Gate Charge	Q_{gs}			9		nC
Gate to Drain “Miller” Charge	Q_{gd}			5		nC
Output Charge	Q_{oss}	V_{DD}=50V, V_{GS}=0V		68		nC
Maximum Continuous Drain to Source Diode Forward Current	I_S				76	A
Maximum Pulsed Drain to Source Diode Forward Current	I_{SM}				304	A

Source to Drain Diode Forward Voltage	V_{SD}	V_{GS}=0V, I_S=76 A		1	1.3	V
Reverse Recovery Time	t_{rr}	V_{GS}=0V, V_{DD}=50V, I_F=76A		58	92	ns
Reverse Recovery Charge	Q_{rr}	dI_F/dt=100A/μs		53	85	nC
Reverse Recovery Time	t_{rr}	V_{GS}=0V, V_{DD}=50V, I_F=76A		51	81	ns
Reverse Recovery Charge	Q_{rr}	dI_F/dt=300A/μs		141	226	nC

Notes:

1. Pulsed Id please refer to Figure 11 & Figure 12 “Forward Bias Safe Operating Area” for more details.

2. E_{AS} of 181 mJ is based on starting T_J= 25°C, L=3 mH, I_{AS}=11 A, V_{DD}=100 V, V_{GS}=10 V. 100% test at L = 0.3 mH, I_{AS}=25 A.

3. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

7.1Typical characteristic



$V_{DS,}$, DRAIN TO SOURCE VOLTAGE (V)

Figure 1: On-Region Characteristics



I_D, DRAIN CURRENT (A)

Figure 2: Normalized On-Resistance vs. Drain Current and Gate Voltage



T_J, JUNCTION TEMPERATURE (°C)

Figure 3: Normalized On Resistance vs. Junction Temperature



V_{GS}, GATE TO SOURCE VOLTAGE (V)

Figure 4: On-Resistance vs. Gate to Source Voltage



V_{GS}, GATE TO SOURCE VOLTAGE (V)

Figure 5: Transfer Characteristics



V_{SD}, BODY DIODE FORWARD VOLTAGE (V)

Figure 6: Source to Drain Diode Forward Voltage vs. Source Current

7.2Typical characteristic



Q_g, GATE CHARGE (nC)

Figure 7: Gate Charge Characteristics



V_{DS}, DRAIN TO SOURCE VOLTAGE (V)

Figure 8: Capacitance vs. Drain to Source Voltage



t_{AV}, TIME IN AVALANCHE (ms)

Figure 9: Unclamped Inductive Switching Capability



T_C, , CASE TEMPERATURE(°C)

Figure 10: Maximum Continuous Drain Current vs Case Temperature



V_{DS}, DRAIN to SOURCE VOLTAGE (V)

Figure 11: Forward Bias Safe Operating Area for FDP8D5N10C



t, PULSE WIDTH (sec)

Figure 12: Single Pulse Maximum Power Dissipation for FDP8D5N10C

7.3Typical characteristic



Figure 13: Junction-to-Case Transient Thermal Response Curve for FDP2D3N10C



Figure 14: Junction-to-Case Transient Thermal Response Curve for FDPF2D3N10C

8.1 TO-220 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	B	B1	C	C1	D	E	F	G
Min	9.7	8.44	1.05	4.8	15.4	12.9	4.28	1.1	0.6	3.4	2.65	5.2
Max	10.3	8.84	1.25	5.2	16.2	13.5	4.68	1.5	1.0	3.8	3.25	5.8

Symbol	H	K	L	L1	M	N	P	Q	T	DIA
Min	0.4	2.9	12.8	2.7	1.15	2.49	2.1	8.7	W:0.35	⊙1.5
Max	0.6	3.3	13.6	3.3	1.35	2.59	2.7	9.3		(deep 0.2)

8.2 TO-220 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	B	C	C2	C3	D	E	G	H	L2	L3
Min	4.30	0.60	0.28	1.17	2.30	8.80	9.80	2.44	28.55	1.10	2.59
Max	4.70	1.00	0.48	1.37	2.70	9.20	10.20	2.64	29.15	1.50	2.89

9.Ordering Information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW FDP8D5N10C	TO-220	1000	Tube and box

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.