UMW IRF7303TR

30V N-Channel MOSFET

1.Description

The SOP-8 has been modified through a customized leadframe for enhan-ced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements,multiple devices can be used in an application with dramatically reduced board space.

2.1Features

- $V_{DS\ (V)}$=30V
- I_D=5.3A
- $R_{DS(ON)}$<50mΩ(V_{GS}=-10)
- $R_{DS(ON)}$<80mΩ(V_{GS}=-4.5V)

2.2Features

- Generation V Technology
- Ultra Low On-Resistance
- Surface Mount
- Dynamic dv/dt Rating
- Fast Switching
- Lead-Free

3.Pinning information

Pin	Symbol	Description
2,4	G1,G2	GATE
1,3	S1,S2	SOURCE
5,6,7,8	D1,D2	DRAIN

SOP-8



4.Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Rating	Units
10 Sec. Pulsed Drain Current, V_{GS}=10V	T_A=25°C	I_D	5.3	A
Continuous Drain Current, V_{GS}=10V	T_A=25°C		4.9	A
Continuous Drain Current, V_{GS}=10V	T_A=70°C		3.9	A
Pulsed Drain Current ①		I_{DM}	20	A
Power Dissipation	T_A=25°C	P_D	2	W
Linear Derating Factor			0.016	W/°C

Gate-to-Source Voltage	V_{GS}	±20	V
Peak Diode Recovery dv/dt ②	dv/dt	5	V/nS
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

5.Thermal Resistance Rating

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ④	$R_{\theta JA}$		62.5	°C/W

6.Electrical Characteristics T_J=25°C

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=250μA, V_{GS}=0V	30			V
Breakdown Voltage Temp. Coefficient	$\Delta V_{(BR)DSS}/T_J$	I_D=1mA,Reference to 25°C		0.032		V/°C
Static Drain-to-Source On-Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=2.4A ③			50	mΩ
		V_{GS}=4.5V, I_D=2A ③			80	
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250μA	1			V
Forward Transconductance	g_{FS}	V_{DS}=15V, I_D=2.4A	5.2			S
Drain-to-Source Leakage Current	I_{DSS}	V_{DS}=24V, V_{GS}=0V			1	μA
		V_{DS}=24V,V_{GS}=0V,T_J=125°C			25	
Gate-to-Source Forward Leakage	I_{GSS}	V_{GS}=20V			100	nA
Gate-to-Source Reverse Leakage		V_{GS}=-20V			-100	
Total Gate Charge	Q_g	I_D=2.4A			25	nC
Gate-to-Source Charge	Q_{gs}	V_{DS}=24V, V_{GS}=10V			2.9	
Gate-to-Drain ("Miller") Charge	Q_{gd}	See Fig. 6 and 12 ③			7.9	
Turn-On Delay Time	$t_{D(on)}$	V_{DD}=15V		6.8		ns
Rise Time	t_r	I_D=2.4A		21		ns
Turn-Off Delay Time	$t_{D(off)}$	R_G=6Ω		22		ns
Fall Time	t_f	R_D=6.2Ω, See Fig. 10 ③		7.7		ns
Internal Drain inductance	L_D	Between lead tip		4		nH
Internal Source inductance	L_S	and center of die contact		6		
Input Capacitance	C_{iss}	V_{GS}=0V		520		pF
Output Capacitance	C_{oss}	V_{DS}=25V		180		pF
Reverse Transfer Capacitance	C_{rss}	f=1.0MHz, See Fig. 5		72		pF

Source-Drain Ratings and Characteristics						
Continuous Source Current (Body Diode)	I_S	MOSFET symbol showing the integral reverse p-n junction diode.			2.5	A
Pulsed Source Current (Body Diode) ①	I_{SM}				20	
Diode Forward Voltage	V_{SD}	T_J=25°C,I_S=1.8A,V_{GS}=0V③			1	V
Reverse Recovery Time	t_{rr}	T_J=25°C, I_F=2.4A		47	71	ns
Reverse Recovery Charge	Q_{rr}	dI/dt=100A/μs ③		56	84	nC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by L_S+L_D)				

Notes:

① Repetitive rating; pulse width limited by max.junction temperature.(See fig.11)

② I_{SD}≤ 2.4A, di/dt ≤ 73A/μS, V_{DD}≤ $V_{(BR)DSS}$,T_J≤ 150°C.

③ Pulse width ≤ 300μs; duty cycle ≤ 2%.

④ Surface mounted on FR-4 board, t ≤ 10sec.

7.1 Typical Characterisitics



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Nomalized On-ResistanceVs. Temperature

7.2 Typical Characterisitics



V_{DS} ,Drain-to-Source Voltage (V)

Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



Q_G, Total Gate Charge (nC)

Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



V_{SD}, Source-to-Drain Voltage (V)

Fig 7. Typical Source-Drain Diode Forward Voltage



V_{DS}, Drain-to-Source Voltage (V)

Fig 8. Maximum Safe Operating Area

7.3 Typical Characterisitics



Fig 9. Maximum Drain Current Vs.AmbientTemperature



Fig 10. Maximum Effective Transient Themal Impedance, Junction-to-Ambient



Fig 11a. Switching Time Test Circuit



Fig 11b. Switching Time Waveforms



Fig 12a. Basic Gate Charge Wavefomm



Fig 12b. Gate Charge Test Circuit

8.SOP-8 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	c	D	E	E1	e	h	L
Min	-	0.05	1.30	0.60	0.39	0.20	4.70	5.80	3.80	1.24	0.30	0.50
Max	1.75	0.20	1.50	0.70	0.47	0.24	5.10	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°

9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW IRF7303TR	SOP-8	3000	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.