UMW NTD4858NT4G

30V N-Channel MOSFET

1.Description

- Low $R_{DS(ON)}$ to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- Optimized Gate Charge to Minimize Switching Losses

2.1Features

- $V_{DS\ (V)}$=30V
- I_D=73A(V_{GS}=10V)
- $R_{DS(ON)}$<6.2mΩ(V_{GS}=10V)
- $R_{DS(ON)}$<9.3mΩ(V_{GS}=4.5V)

2.2Features

- VCORE Applications
- DC-DC Converters
- High/Low Side Switching

3.Pinning information

Pin	Symbol	Description
1	G	GATE
2	D	DRAIN
3	S	SOURCE

TO-252(DPAK)
top view





4.Absolute Maximum Ratings T_J= 25°C

Parameter			Symbol	Value	Units
Drain−to−Source Voltage			V_{DSS}	30	V
Gate−to−Source Voltage			V_{GS}	±20	V
Continuous Drain Current ($R_{\theta JA}$) (Note 1)	Steady State	T_A=25°C	I_D	14	A
		T_A=85°C		10.9	A
Power Dissipation ($R_{\theta JA}$) (Note 1)		T_A=25°C	P_D	2	W
Continuous Drain Current ($R_{\theta JA}$) (Note 2)		T_A=25°C	I_D	11.2	A
		T_A=85°C		8.7	A
Power Dissipation ($R_{\theta JA}$) (Note 2)		T_A=25°C	P_D	1.3	W

Continuous Drain Current ($R_{\theta JC}$) (Note 1)	Steady State	T_C=25°C	I_D	73	A
		T_C=85°C		56	A
Power Dissipation ($R_{\theta JC}$) (Note 1)		T_C=25°C	P_D	54.5	W
Pulsed Drain Current	t_p=10μs	T_C=25°C	I_{DM}	146	A
Curent Limited by Package		T_A=25°C	$I_{DmaxPkg}$	45	A
Junction and Storage Temperature		T_A=25°C	T_J,T_{STG}	−55 to 175	°C
Source Current (Body Diode)			I_S	45	A
Drain to Source dv/dt			dv/dt	6	V/ns
Single Pulse Drain−to−Source Avalanche Energy (T_J=25°C ,V_{DD}=50V, V_{GS}=10V, I_L=15A_{pk}, L=1mH, R_G=25 Ω)			E_{AS}	112.5	mJ
Lead Temperature for Soldering Purposes (1/8” from case for 10 s)			T_L	260	°C

5.Thermal resistance rating

Parameter	Symbol	Value	Units
Junction-to-Case (Drain)	$R_{\theta JC}$	1.9	°C/W
Junction-to-TAB (Drain)	$R_{\theta JC\text{-}TAB}$	3.5	°C/W
Junction-to-Ambient-Steady State (Note 1)	$R_{\theta JA}$	56.6	°C/W
Junction-to-Ambient-Steady State (Note 2)	$R_{\theta JA}$	106.6	°C/W

6.Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V, I_D=250μA		30			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$				22		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=0V	T_J=25°C			1	μA
		V_{DS}=20V	T_J=125°C			10	μA
Gate−to−Source Leakage Current	I_{GSS}	V_{DS}=0V, V_{GS}=±20V				±100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250μA		1.45		2.5	V
Negative Temperature Coefficient	$V_{GS(th)}/T_J$				5.3		mV/°C
Drain−to−Source On Resistance	$R_{DS(ON)}$	V_{GS}=10V	I_D=30A		5.2	6.2	mΩ
		V_{GS}=4.5V	I_D=30A		7.3	9.3	mΩ
Forward Transconductance	g_{FS}	V_{DS}=1.5V, I_D=15A			55		S
CHARGES AND CAPACITANCES							
Input Capacitance	C_{iss}	V_{GS}=0V, V_{DS}=12V, f=1MHz			1563		pF
Output Capacitance	C_{oss}				405		pF
Reverse Transfer Capacitance	C_{rss}				200		pF
Total Gate Charge	$Q_{G(TOT)}$	V_{GS}=4.5V, V_{DS}=15V, I_D=30A			12.8	19.2	nC
Threshold Gate Charge	$Q_{G(TH)}$				1.3		nC
Gate-to-Source Charge	Q_{GS}				4.7		nC
Gate-to-Drain Charge	Q_{GD}				5.2		nC
Total Gate Charge	$Q_{G(TOT)}$	V_{GS}=10V, V_{DS}=15V, I_D=30A			25.7		nC

1. Surface−mounted on FR4 board using 1 sq−in pad, 1 oz Cu.
2. Surface−mounted on FR4 board using the minimum recommended pad size.

SWITCHING CHARACTERISTICS (Note 4)						
Turn-On Delay Time	$t_{D(on)}$	V_{GS}=4.5V, V_{DS}=15V I_D=15A, R_G=3Ω		12.6		ns
Rise Time	t_r			20.2		ns
Turn-Off Delay Time	$t_{D(off)}$			16.4		ns
Fall Time	t_f			5.1		ns
Turn-On Delay Time	$t_{D(on)}$	V_{GS}=11.5V, V_{DS}=15V I_D=15A, R_G=3Ω		7.7		ns
Rise Time	t_r			17.3		ns
Turn-Off Delay Time	$t_{D(off)}$			23.8		ns
Fall Time	t_f			2.8		ns
DRAIN−SOURCE DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{SD}	V_{GS}=0V I_D=30A	T_J=25°C	0.87	1.2	V
			T_J=125°C	0.73		V
Reverse Recovery Time	t_{rr}	V_{GS}=0V, dIs/dt=100A/μs I_S=30A		11.6		ns
Charge Time	t_a			7.8		ns
Discharge Time	t_b			3.7		ns
Reverse Recovery Time	Q_{rr}			3		nC
PACKAGE PARASITIC VALUES						
Source Inductance	L_S	T_A=25°C		2.49		nH
Drain inductance, DPAK	L_D			0.0164		nH
Drain Inductance, IPAK	L_D			1.88		nH
Gate Inductance	L_G			3.46		nH
Gate Resistance	R_G			0.7		Ω

3. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.

4. Switching characteristics are independent of operating junction temperatures.

7.1Typical Characterisitics



Figure 1: On−Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On−Resistance vs. Gate−to−Source Voltage



Figure 4: On−Resistance versus Drain Current and Gate Voltage



Figure 5: On−Resistance Variation with Temperature



Figure 6: Drain−To−Source Leakage Current versus Voltage

7.2Typical Characterisitics



Figure 7: Capacitance Variation



Figure 8: Gate−To−Source and Drain−To−Source Voltage vs. Total Charge



Figure 9: Resistive Switching Time Variation vs. Gate Resistance



Figure 10: On−Resistance versus Drain Current and Gate Voltage



Figure 11: Maximum Rated Forward Biased Safe Operating Area



Figure 12: Maximum Avalanche Energy vs. Starting Junction Temperature

7.3Typical Characterisitics



Figure 13: Thermal Response

8.TO-252 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A1	A2	A3	b	c	D	D1	D2	E	E1	E2	e	L1	L2	L3	θ
Min	0.00	2.18	0.90	0.65	0.46	6.35	4.95	4.32	9.40	5.97	5.21	2.286	0.89	1.70	0.60	0.00
Max	0.13	2.39	1.10	0.85	0.61	6.73	5.46	4.90	10.41	6.22	5.38	BSC	1.27	1.90	1.00	8.00

9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW NTD4858NT4G	TO-252	2500	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.