1.Description

The OP2177/4177 family consists of very high precision, single, dual,and quad amplifiers featuring extremely low offset voltage and drift, low input bias current, low noise, and low power consump-tion. Outputs are stable with capacitive loads of over 1000 pF with no external compensation. Supply current is less than 500 µA per amplifier at 30 V. Internal 500 Ω series resistors protect the inputs, allowing input signal levels several volts beyond either supply without phase reversal.

2.Applications

- Wireless base station control circuits
- Optical network control circuits
- Instrumentation
- Sensors and controls

  Thermocouples

  Resistor thermal detectors (RTDs)

  Strain bridges

  Shunt current measurements
- Precision filters

3.Features

- Low offset voltage: 60 µV maximum
- Very low offset voltage drift: 0.7µV/°C maximum Low input bias current: 2 nA maximum
- Low noise: 8 nV/√Hz typical
- CMRR, PSRR, and AVO > 120 dB minimum
- Low supply current: 400 µA per amplifier
- Dual supply operation: ±2.5V to ±15V

  Unity-gain stable
- No phase reversal
- Inputs internally protected beyond supply voltage

4.Pinning Information



SOP-14



SOP-8

5.Absolute Maximum Ratings

Description	Rating
Supply Voltage	36V
Input Voltage	V_{S-} to V_{S+}
Differential input Voltage	±Supply Voltage
Storage Temperature Range R, RM, and RU Packages	−65°C to +150°C
Operating Temperature Range OP1177/OP2177/OP4177	−40°C to +125°C
Junction Temperature Range R, RM, and RU Packages	−65°C to +150°C
Lead Temperature, Soldering (10 sec)	300°C

6.1Electrical Characteristics

V_S=±5.0V, V_{CM}=0V, T_A=25°C, unless otherwise noted.

Parameter		Symbol	Conditions	Min	Typ	Max	Units
Offset Voltage	OP2177/OP4177	V_{OS}			15	75	μV
	OP2177		−40°C <T_A<+125°C		25	100	μV
	OP4177		−40°C <T_A<+125°C		25	120	μV
Input Bias Current		I_B	−40°C <T_A<+125°C	-2	0.5	2	nA
Input Offset Current		I_{OS}T	−40°C <T_A<+125°C	-1	0.2	1	nA
Input Voltage Range				-3.5		3.5	V
Common-Mode Rejection Ratio		CMRR	V_{CM}=-3.5 V to +3.5 V	120	126		dB
			−40°C<T_A<+125°C	118	125		dB
Large Signal Voltage Gain		A_{VO}	R_L=100kΩ to V_{CM}, V_O= −3.5V to 3.5V	1000	2000		V/mV
Offset Voltage Drift							
OP2177		$\Delta V_{OS}/\Delta T$	−40°C<T_A<+125°C		0.2	0.7	μV/°C
OP4177		$\Delta V_{OS}/\Delta T$	−40°C<T_A<+125°C		0.3	0.9	μV/°C
Output Voltage High		V_{OH}	I_L=1mA, −40°C<T_A<+125°C	4	4.1		V
Output Voltage Low		V_{OL}	I_L=1mA, −40°C<T_A<+125°C		-4.1	-4	V
Output Current		I_{OUT}	$V_{DROPOUT}$<1.2V		±10		mA
Power Supply Rejection Ratio							
OP2177/OP4177		PSRR	V_S=±2.5V to ±15V	118	121		dB
			−40°C<T_A<+125°C	114	120		dB
Supply Current per Amplifier		I_{SY}	V_O=0V		400	500	μA
			−40°C<T_A<+125°C		500	600	μA
Slew Rate		SR	R_L=2kΩ		0.7		V/μs
Gain Bandwidth Product		GBP			1.3		MHz
Voltage Noise		e_np-p	0.1Hz to 10Hz		0.4		μV_{p-p}
Voltage Noise Density		e_n	f=1kHz		7.9	8.5	nV/√Hz
Current Noise Density		i_n	f=1kHz		0.2		pA/√Hz
Multiple Amplifiers		C_S	DC		0.01		μV/V
Channel Separation			f=100kHz		-120		dB

6.2Electrical Characteristics

V_S=±15V, V_{CM}=0V, T_A=25°C, unless otherwise noted.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Offset Voltage						
OP2177/OP4177	V_{OS}			15	75	μV
OP2177	V_{OS}	−40°C <T_A<+125°C		25	100	μV
OP4177	V_{OS}	−40°C <T_A<+125°C		25	120	μV
Input Bias Current	I_B	−40°C <T_A<+125°C	-2	0.5	2	nA
Input Offset Current	I_{OS}	−40°C <T_A<+125°C	-1	0.2	1	nA
Input Voltage Range			-13.5		13.5	V
Common-Mode Rejection Ratio	CMRR	V_{CM}=-13.5 V to +13.5 V				
		−40°C<T_A<+125°C	120	125		dB
Large Signal Voltage Gain	A_{VO}	R_L=2kΩ to V_{CM}, V_O= −13.5V to 13.5V	1000	3000		V/mV
Offset Voltage Drift						
OP2177	$\Delta V_{OS}/\Delta T$	−40°C<T_A<+125°C		0.2	0.7	μV/°C
OP4177	$\Delta V_{OS}/\Delta T$	−40°C<T_A<+125°C		0.3	0.9	μV/°C
Output Voltage High	V_{OH}	I_L=1mA, −40°C<T_A<+125°C	14	14.1		V
Output Voltage Low	V_{OL}	I_L=1mA, −40°C<T_A<+125°C		-14.1	-14	V
Output Current	I_{OUT}	$V_{DROPOUT}$<1.2V		±10		mA
Short-Circuit Current	I_{SC}			±25		mA
Power Supply Rejection Ratio						
OP2177/OP4177	PSRR	V_S=±2.5V to ±15V	118	121		dB
		−40°C<T_A<+125°C	114	120		dB
Supply Current per Amplifier	I_{SY}	V_O=0V		400	500	μA
		−40°C<T_A<+125°C		500	600	μA
Slew Rate	SR	R_L=2kΩ		0.7		V/μs
Gain Bandwidth Product	GBP			1.3		MHz

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Voltage Noise	e_np-p			0.4		μV_{p-p}
Voltage Noise Density	e_n	0.1Hz to 10Hz		7.9	8.5	nV/√Hz
Current Noise Density	i_n	f=1kHz		0.2		pA/√Hz
Multiple Amplifiers Channel Separation	C_S	f=1kHz		0.01		μV/V
		DC				
		f=100kHz		-120		dB

7.1Typical Characteristic



Figure 1: Input Offset Voltage Distribution



Figure 2: Output Voltage to Supply Rail vs. Load Current



Figure 3: Input Offset Voltage Drift Distribution



Figure 4: Input Bias Current vs. Temperature



Figure 5: Input Bias Current Distribution



Figure 6: Open-Loop Gain and Phase Shift vs. Frequency

7.2Typical Characteristic



Figure 7: Closed-Loop Gain vs. Frequency



Figure 8: Small Signal Transient Response



Figure 9: Output Impedance vs. Frequency



Figure 10: Small Signal Overshoot vs. Load Capacitance



Figure 11: Large Signal Transient Response



Figure 12: Positive Overvoltage Recovery

7.3Typical Characteristic



Figure 13: Negative Overvoltage Recovery



Figure 14: 0.1 Hz to 10 Hz Input Voltage Noise



Figure 15: CMRR vs. Frequency



Figure 16: Voltage Noise Density vs. Frequency



Figure 17: PSRR vs. Frequency



Figure 18: Short-Circuit Current vs. Temperature

7.4Typical Characteristic



Figure 19: Output Voltage Swing vs. Temperature



Figure 20: CMRR vs. Temperature



Figure 21: Warm-Up Drift



Figure 22: PSRR vs. Temperature



Figure 23: Input Offset Voltage vs. Temperature



Figure 24: Input Offset Voltage Distribution

7.5Typical Characteristic



Figure 25: Output Voltage to Supply Rail vs. Load Current



Figure 26: Output Impedance vs. Frequency



Figure 27: Open-Loop Gain and Phase Shift vs. Frequency



Figure 28: Large Signal Transient Response



Figure 29: Closed-Loop Gain vs. Frequency



Figure 30: Small Signal Transient Response

7.6Typical Characteristic



Figure 31: Small Signal Overshoot vs. Load Capacitance



Figure 32: No Phase Reversal



Figure 33: Positive Overvoltage Recovery



Figure 34: CMRR vs. Frequency



Figure 35: Negative Overvoltage Recovery



Figure 36: PSRR vs. Frequency

7.7Typical Characteristic



Figure 37: 0.1 Hz to 10 Hz Input Voltage Noise



Figure 38: Output Voltage Swing vs. Temperature



Figure 39: Voltage Noise Density vs. Frequency



Figure 40: Input Offset Voltage vs. Temperature



Figure 41: Short-Circuit Current vs. Temperature



Figure 42: Supply Current vs. Temperature

7.8Typical Characteristic



Figure 43: Supply Current vs. Supply Voltage



Figure 44: Channel Separation vs. Frequency

8.1SOP-8 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	b	c	D	E	E1	e	L	θ
Min	1.350	0.000	1.350	0.330	0.170	4.700	3.800	5.800	1.270	0.400	0°
Max	1.750	0.100	1.550	0.510	0.250	5.100	4.000	6.200	BSC	1.270	8°

8.2SOP-14 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	C	D	E	E1	e	h	L
Min	-	0.05	1.35	0.65	0.203	0.17	8.45	5.80	3.80	1.24	0.25	0.40
Max	1.75	0.25	1.55	0.75	0.305	0.25	8.85	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°

9.Ordering Information

SOP-8



SOP-14



yy: Year Code
ww: Week Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW OP2177ARZ	OP2177	SOP-8	2500	Tape and reel
UMW OP4177ARZ	OP4177	SOP-14	2500	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.