

1.Description

The SMxxOC Series is designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.


2.Features

- 130 Watts Peak Pulse Power per (8/20 μ s)
- IEC61000-4-2 (ESD) ± 15 kV (air), ± 8 kV (contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)
- Protects two bidirectional line
- Low clamping voltage
- Low leakage current
- Working voltages : 5.0V, 12V
- Meets MSL 1 Requirements

3.Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Networking and Telecom
- Serial and Parallel Ports
- Quick charger

4.Pinning information



SOT-23



5. Absolute Maximum Ratings

Parameter	Symbol	Value	Units
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 20	kV
Peak Pulse Power($t_p=8/20\mu s$ waveform)	P_{PP}	130	W
Junction Temperature	T_{OPT}	-55 to 150	$^{\circ}C$
Storage Temperature	T_{STG}	-55 to 150	$^{\circ}C$
Lead Solder Temperature – Maximum (10 Second Duration)	T_L	260 (10 sec.)	$^{\circ}C$



6.Electrical Characteristics(T_A=25°C)

PART NUMBER	DEVICE MARKING	V _{RWM}	V _B	I _T	V _{C@1A}	V _C		I _R	C _T
		(V)	(V)	(mA)	(V)	(V)		(μA)	(pF)
		(max.)	(min.)		(max.)	(max.)	(@A)	(max.)	(max.)
UMW SM05OC	CO05	5	5.6	1	8.5	16	8	1	15
UMW SM12OC	CO12	12	13.3	1	19	26	5	0.2	15

Notes: The above data are for reference only.




7. Typical characteristic

Figure 1: 8/20µs Waveform per IEC61000-4-5	Figure 2: Contact Discharge Current Waveform per IEC 61000-4-2)
Figure 3: Voltage vs Capacitance	Figure 4: Peak Pulse Current vs Clamping Voltage



8.SOT-23 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	B	b _p	C	D	E	H _E	A1	L _p
Min	0.95	1.78	0.35	0.08	2.70	1.20	2.20	0.013	0.20
Max	1.40	2.04	0.50	0.19	3.10	1.65	3.00	0.100	0.50



9.Ordering information



yww: Batch Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW SM05OC	CO05	SOT-23	3000	Tape and reel
UMW SM12OC	CO12	SOT-23	3000	Tape and reel



10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.