

1. Description

The AZ5123-01H is designed to protect voltage sensitive components from damage or latch-up due to ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed to ESD for board level. Because of its small size and bi-directional design, it is ideal for use in cellular phones, MP3 players, and portable applications that require audio line protection.

3. Applications


- Cellular handsets and accessories
- Portable digital assistants
- Notebooks & handhelds

2. Features

- IEC 61000-4-2 Level 4 ESD Protection
- - $\pm 25\text{kV}$ Contact Discharge
- - $\pm 25\text{kV}$ Air Discharge
- 50W Peak pulse Power (8/20us)
- Low clamping voltage
- Working voltage: 3.3V
- Low leakage current
- RoHS compliant
- Protecting one bi-directional lines
- Junction capacitance: 12pF Typ

- Digital cameras
- MP3 players
- Peripherals

4. Pinning information



SOD-523



5. Absolute Maximum Ratings


Parameter	Symbol	Min.	Max.	Units
Peak pulse power ($t_p=8/20\mu s$)@25°C	P_{PK}		50	W
Peak pulse current ($t_p=8/20\mu s$)@25°C	I_{PP}		8	A
ESD (IEC61000-4-2 air discharge) @25°C	V_{ESD}		±25	kV
ESD (IEC61000-4-2 contact discharge) @25°C			±25	kV
Junction temperature	T_J		150	°C
Operating temperature	T_{OP}	-40	125	°C
Storage temperature	T_{STG}	-55	150	°C
Lead temperature	T_L		260	°C



6.Electrical Characteristic (T_A=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Reverse Stand-off Voltage	V _{RWM}				3.3	V
Reverse Breakdown Voltage	V _{BR}	I _T =1mA	3.8			V
Reverse Leakage Current	I _R	V _{RWM} =3.3V			1	μA
Clamping Voltage	V _C	I _{PP} =1A(8 x 20μs pulse)		6		V
Clamping Voltage	V _C	I _{PP} =8A(8 x 20μs pulse)		10		V
Junction Capacitance	C _J	V _R =0V, f=1MHz, I/O to GND		15		pF


7.Portion Electronics Parameter



Symbol	Parameter
V _{RWM}	Peak Reverse Working Voltage
I _R	Reverse Leakage Current @ V _{RWM}
V _{BR}	Breakdown Voltage @ I _T
I _T	Test Current
I _{PP}	Maximum Reverse Peak Pulse Current
V _C	Clamping Voltage @ I _{PP}




8. Typical characteristic





9.SOD-523 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b _p	C	D	E	H _E	θ
Min	0.58	0.3	0.100	1.15	0.75	1.5	5°
Max	0.68	0.4	0.135	1.25	0.85	1.7	



10.Ordering information



Order Code	Package	Base QTY	Delivery Mode
UMW AZ5123-01H	SOD-523	3000	Tape and reel



11.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.