


1. Descriptions

The ESD56151Wxx is a transient voltage suppressor designed to protect power interfaces. It is suitable to replace multiple discrete components in portable electronics. The ESD56151Wxx is specifically designed to protect power lines.

2. Features

- Reverse stand-off voltage: 4.5V ~ 5V
- Surge protection according to IEC61000-4-5 see Table 4
- ESD protection according to IEC61000-4-2 $\pm 30\text{kV}$ (contact and air discharge)
- Low clamping voltage
- Solid-state silicon technology

3. Pinning information




SOD-323

4. Absolute Maximum Ratings $T_A = 25^\circ\text{C}$

Parameter	Symbol	Maximum	Units
Peak Pulse Power ($t_p=8/20\text{s}$)	P_{PK}	2400	W
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	kV
Junction Temperature	T_J	125	$^\circ\text{C}$
Operating temperature	T_{OP}	-40 to 85	$^\circ\text{C}$
Lead temperature	T_L	260	$^\circ\text{C}$
Storage temperature	T_{STG}	-55 to 150	$^\circ\text{C}$



5. Electrical Characteristic ($T_A=25^\circ\text{C}$ unless otherwise noted)



Definitions of electrical characteristics



6. Electrical Characteristic ($T_A=25^\circ\text{C}$ unless otherwise noted)

Type number	V_{RWM} (V)	Breakdown voltage $V_{BR}(V)$ $I_{BR}=1\text{mA}$			Reverse leakage current $I_{RM}(\mu\text{A})$ at V_{RWM}		Junction capacitance $F=1\text{MHz}$, $V_R=0\text{V}(\text{pF})$	
	Max.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.
ESD56151W04	4.5	4.7	5.3	6.4		0.1	280	350
ESD56151W05	5	5.3	6.3	7.1		0.1	400	450

Type number	Rated peak pulse current I_{PP} (A) ¹⁾³⁾	Clamping voltage $V_{CL}(V)$ at $I_{PP}(A)$ ¹⁾³⁾	Clamping voltage $V_{CL}(V)$ at $I_{PP}=16\text{A}$, $t_p=100\text{ns}$ ²⁾³⁾	Clamping voltage $V_{CL}(V)$ at $V_{ESD} = 8\text{kV}$ ²⁾³⁾
ESD56151W04	150	16	6.5	7
ESD56151W05	145	16	6.7	7.5

Notes:

- 1) Non-repetitive current pulse, according to IEC61000-4-5. (8/20 μs current waveform)
- 2) Non-repetitive current pulse, according to IEC61000-4-2.
- 3) Measured from pin 1 to pin 2.



7. Typical characteristic




Figure 1: 8/20μs waveform per IEC61000-4-5




Figure 2: Contact discharge current waveform per IEC61000-4-2




Figure 3: Clamping voltage vs. Peak pulse current




Figure 4: Capacitance vs. Reverse voltage




Figure 5: Non-repetitive peak pulse power vs. Pulse time





Figure 6: Power derating vs. Ambient temperature



8.SOD-323 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b_p	C	D	E	H_E	A_1	p
Min	0.90	0.25	0.10	1.60	1.15	2.30	0.01	0.20
Max	1.20	0.40	0.15	1.80	1.35	2.80	0.10	0.50



9.Ordering information



Order Code	Package	Base QTY	Delivery Mode
UMW ESD56151W04	SOD-323	3000	Tape and reel
UMW ESD56151W05	SOD-323	3000	Tape and reel



10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.