

1.Description

The UMW ESDA8V2-1J is a unidirectional single line Transil diode designed specifically for the protection of integrated circuits in portable equipment and miniaturized electronic devices subject to EOS and ESD transient over voltages.

3.Features

- Breakdown voltage $V_{BR}=8.2V$
- Unidirectional device
- High peak power dissipation: 500W
(8/20 μs waveform)
- ESD protection level better than IEC 61000-4-2 level 4: 30 kV contact discharge

4.Benefits


- High EOS and ESD protection level
- High integration

2.Applications

- Computers
- Printers
- Communication systems
Cellular phone handsets and accessories
- Video equipment

- Low leakage current ($< 0.5 \mu A @ 5 V$)
- IEC 61000-4-2 level 4
 - $\pm 15 kV$ (air discharge)
 - $\pm 8 kV$ (contact discharge)
- MIL STD 883G - Method 3015-7: class 3B
 - HBM (human body model): $\geq 8kV$

5.Pinning information



SOD-323



6. Absolute Maximum Ratings $T_A = 25^\circ\text{C}$

Parameter		Symbol	Value	Units
ESD discharge: IEC 61000-4-2 air discharge on input pin			± 30	kV
IEC 61000-4-2 contact discharge on input pin		V_{PP}	± 30	kV
MIL STD 883G - Method 3015-7: class 3B			± 30	kV
Peak pulse power dissipation (8/20 μs) ⁽¹⁾	$T_{J\text{ initial}} = T_{\text{amb}}$	P_{PP}	500	W
Peak pulse current (8/20 μs)		I_{PP}	25	A
Junction temperature range		T_J	-40 to 125	$^\circ\text{C}$
Storage temperature range		T_{STG}	-55 to 150	$^\circ\text{C}$
Maximum lead temperature for soldering during 10s		T_L	260	$^\circ\text{C}$

Notes:


For a surge greater than the maximum values, the diode will fail in short-circuit.



7. Electrical Characteristic ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Breakdown Voltage	V_{BR}	$I_R=1\text{mA}$	8.2			V
Leakage current @ V_{RM}	I_{RM}	$V_{RWM}=5\text{V}$		0.1	0.5	μA
		$I_{PP}=1\text{A}$			11	V
Clamping voltage (8/20 μs waveform)	V_{CL}	$I_{PP}=5\text{A}$			13	V
		$I_{PP}=25\text{A}$			20	V
Input capacitance	C	$V_R=0\text{V}$, $F_{osc}=1\text{MHz}$, $V_{osc}=30\text{mV}$		210	250	pF

8. Electrical Parameters ($T_A=25^\circ\text{C}$ unless otherwise noted)



Symbol	Parameter
V_{BR}	Breakdown voltage
I_{RM}	Leakage current @ V_{RM}
V_{RM}	Stand-of voltage
V_{CL}	Clamping voltage
I_{PP}	Peak pulse current
C	Input capacitance



9.1 Typical characteristic




Figure 1: Relative variation of peak pulse power versus initial junction temperature




Figure 2: Peak pulse power versus exponential pulse duration




Figure 3: Clamping voltage versus peak pulse current (typical values, exponential waveform)




Figure 4: Forward voltage drop versus peak forward current (typical values)




Figure 5: Junction capacitance versus reverse voltage applied (typical values)






Figure 6: Relative variation of leakage current versus junction temperature (typical values)




9.2Typical characteristic

	
Figure 7: ESD response to IEC 61000-4-2 (+15 kV air discharge)	Figure 8: ESD response to IEC 61000-4-2 (-15 kV air discharge)



10.SOD-323 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b_p	C	D	E	H_E	A_1	P
Min	0.90	0.25	0.10	1.60	1.15	2.30	0.01	0.20
Max	1.20	0.40	0.15	1.80	1.35	2.80	0.10	0.50



11.Ordering information



Order Code	Package	Base QTY	Delivery Mode
UMW ESDA8V2-1J	SOD-323	3000	Tape and reel



12.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.