

1.Features

- Unidirectional ESD protection of one line
- Low diode capacitance: $C_d=25\text{pF}$
- Low clamping voltage: $V_{CL}=12\text{V}$
- Very low leakage current: $I_{RM}=10\text{nA}$
- ESD protection up to 26kV
- IEC 61000-4-2; level 4 (ESD)
- AEC-Q101 qualified

3.Applications

- Computers and peripherals
- Audio and video equipment
- Cellular handsets and accessories
- Communication systems
- FireWire


2.Mechanical Characteristics

- SOD-882 package
- Marking: Marking Code
- Packaging: Tape and Reel per EIA4 81
- RoHS/WEEE Compliant
- Molding compound flammability rating: UL94 V-0

4.Pinning information

Pin	Symbol	Description
1	C	Cathode
2	A	Anode

SOD-323



5. Quick reference data

$T_{amb}=25^{\circ}\text{C}$ unless otherwise specified.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
reverse standoff voltage	V_{RWM}				5	V
diode capacitance	C_d	$V_R=0\text{V}$, $f=1\text{MHz}$		25	30	pF



6. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Parameter	Symbol	Conditions	Min	Typ	Max	Units
peak pulse power	P_{PP}	$t_p=8/20\mu s$ ①②			42	W
peak pulse current	I_{PP}	$t_p=8/20\mu s$ ①②			3.5	A
junction temperature	T_J				150	°C
ambient temperature	T_{amb}		-55		150	°C
storage temperature	T_{STG}		-65		150	°C

Notes:

- ① Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC 61000-4-5.
 ② Measured from pin 1 to pin 2.

7. ESD maximum ratings

$T_{amb}=25^{\circ}C$ unless otherwise specified.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
electrostatic discharge voltage	V_{ESD}	IEC 61000-4-2 (contact discharge) ①			26	kV
		machine model			400	V
		MIL-STD-883 (human body model)			10	kV

Notes:

- ① Device stressed with ten non-repetitive ESD pulses.

8. ESD standards compliance

Parameter	Conditions
IEC 61000-4-2; level 4 (ESD)	> 15 kV (air); > 8 kV (contact)
MIL-STD-883; class 3 (human body model)	> 4 kV



9. Electrical Characteristic ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
reverse standoff voltage	V_{RWM}				5	V
reverse leakage current	I_{RM}	$V_{\text{RWM}}=5\text{V}$		10	100	nA
breakdown voltage	V_{BR}	$I_{\text{R}}=5\text{mA}$	6.4	6.8	7.2	V
diode capacitance	C_{d}	$V_{\text{R}}=0\text{V}$, $f=1\text{MHz}$		25	30	pF
clamping voltage	V_{CL}	①②				
		$I_{\text{PP}}=1\text{A}$			9	V
		$I_{\text{PP}}=3.5\text{A}$			12	V
differential resistance	r_{dif}	$I_{\text{R}}=5\text{mA}$			30	Ω
forward voltage	V_{F}	$I_{\text{F}}=200\text{mA}$			1.2	V





Notes:

① Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC 61000-4-5.

② Measured from pin 1 to pin 2.







10.1Typical characteristic

	
Figure 1: 8/20 μ s pulse waveform according to IEC 61000-4-5	Figure 2: ESD pulse waveform according to IEC 61000-4-2
	
Figure 3: Diode capacitance as a function of reverse voltage; typical values	Figure 4: V-I characteristics for a unidirectional ESD protection diode




10.2Typical characteristic


	
Figure 5: unclamped +8 kV ESD pulse waveform (IEC 61000-4-2 network)	Figure 6: clamped +8 kV ESD pulse waveform (IEC 61000-4-2 network) pin 1 to 2
	
Figure 7: unclamped -8 kV ESD pulse waveform (IEC 61000-4-2 network)	Figure 8: clamped -8 kV ESD pulse waveform (IEC 61000-4-2 network) pin 1 to 2




11.SOD-323/SOD-523/SOD-882 Package Outline Dimensions



PESD5V0L1UA (SOD323)




PESD5V0L1UB (SOD523)





12.Ordering information



yww: Batch Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW PESD5VOL1UA	1J	SOD-323	3000	Tape and reel
UMW PESD5VOL1UB	Z8	SOD-523	3000	Tape and reel
UMW PESD5VOL1UL	XY	SOD-882	10000	Tape and reel



13.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.