1.Description

TPD 4E1U06 Is an electrostatic discharge (ESD) protection diode based on a four-channel one-way transient voltage suppressor (TVS), with ultra-low capacitance. The ESD shock dissipation value of this device is higher than the highest level stipulated by the IEC 61000-4 -2 international standard.

2.Application

- USB 2.0
- Ethernet
- Differential signaling (LVDS)
- HD Multimedia interface (HDMI) control line Mobile
- industry processor interface (MIPI) bus Low Pressure

3.Features

- IEC 61000-4-2 4 ESD protection
  – ± 15kV, with contact discharge
  – ± 15kV, air-gap discharge
- IEC61000-4-4 Transient discharge (EFT) protection
  – 80A (5/50ns)
- IEC61000-4-5 Surge protection
  – 3A (8/20μ s)
- IO capacitance: 0.8 pF (typical value)
- DC breakdown voltage: 6.5V (minimum)
- Ultra-low leakage current: 10 nA (max.)
- Low ESD clamp voltage
- easy-to-wire DCK and DBV packages
- Industrial temperature range:-40°C to 125°C Small

4.Pinning information



5.Pin Configuration and Functions



DCK Package 6-Pin
SC70-6 Top View



DBV Package 6-Pin
SOT-23 Top View

PIN		I/O	DESCRIPTION
NAME	NO		
D1+	1	I/O	ESD protected channel. Connect to data line as close to the connector as possible
D1-	6	I/O	
D2-	4	I/O	
D2+	3	I/O	
GND	2	GND	Ground. Connect to ground
NC	5	I/O	No connect. Can be left floating, grounded, or connected to V_{CC}

6.Absolute Maximum Ratings

Parameter	Symbol	MIN	MAX	Units
IEC 61000-4-4 EFT protection (5/50 ns)			80	A
IEC 61000-4-5 surge protection (8/20 μs) peak pulse current	I_{PP}		3	A
IEC 61000-4-5 surge protection (8/20 μs) peak pulse power	P_{PP}		45	W
Junction temperature		-40	125	°C
Storage temperature	T_{STG}	-65	115	°C

7.ESD Ratings

		Value	Units
$V_{(ESD)}$ Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins(1)	±4000	V
	Charged device model (CDM), per JEDEC specification JESD22-C101 all pins(2)	±1500	V

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

8.ESD Ratings - IEC Specification

		Value	Units
$V_{(ESD)}$ Electrostatic discharge	IEC 61000-4-2 contact ESD	±15000	V
	IEC 61000-4-2 air-gap ESD	±15000	V

9.Recommended Operating Conditions

		MIN	MAX	Units
V_{IO}	Input pin voltage	0	5.5	V
T_A	Operating free-air temperature	-40	125	°C

over operating free-air temperature range (unless otherwise noted)

10.Thermal Information

THERMAL METRIC[1]	Symbol	DBV (SOT-23)	DCK (SC-70)	Units
		6 PINS	6 PINS	
Junction-to-ambient thermal resistance	$R_{\theta JA}$	224.3	274.3	°C/W
Junction-to-case (top) thermal resistance	$R_{\theta JC(top)}$	166.1	113.8	°C/W
Junction-to-board thermal resistance	$R_{\theta JB}$	68.4	76.7	°C/W
Junction-to-top characterization parameter	Ψ_{JT}	57.3	3.6	°C/W
Junction-to-board characterization parameter	Ψ_{JB}	67.9	75.9	°C/W

11.Electrical Characteristic (T_A=25°C unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Reverse stand-off voltage	V_{RWM}	I_{IO}=10μA				5.5	V
Clamp voltage with ESD strike	V_{CLAMP}	I_{PP}=1A,tp=8/20μs,from I/O to GND(1)			11		V
		I_{PP}=3A,tp=8/20μs,from I/O to GND(1)			15		V
Dynamic resistance	R_{DYN}	Pin x to GND pin(2)			1		Ω
		GND to pin x			0.6		Ω
Line capacitance	C_L	f=1MHz, V_{BIAS}=2.5V, 25°C			0.8	1	pF
Channel to channel input capacitance	C_{CROSS}	Pin2=0V, f=1MHz, V_{BIAS}=2.5V between channel pins	DCK package		0.006	0.015	pF
			DBV package		0.01	0.025	pF
Variation of channel input capacitance	$\Delta_{CIO\text{-}TO\text{-}GND}$	Pin2=0V,f=1MHz,V_{BIAS}=2.5V, channel_x pin to ground – channel_y pin to ground			0.025	0.07	pF
Break-down voltage, IO to GND	V_{BR}	I_{IO}=1mA		6.5		8.5	V
Leakage current	I_{LEAK}	V_{IO}=2.5V			1	10	nA

(1) Non-repetitive current pulse 8/20 μs exponentially decaying waveform according to IEC61000-4-5.

(2) Extraction of RDYN using least squares fit of TLP characteristics between I = 10 A and I = 20 A.

12.1Typical characteristic



Figure 1: TLP, Data to GND



Figure 2: TLP, GND to Data



Figure 3: IEC 61000-4-2 Clamping Voltage, 8-kV Contact



Figure 4: Capacitance



Figure 5: Diode Curve



Figure 6: I_{LEAK} vs Temperature

12.2Typical characteristic



Figure 7: Capacitance Across V_{BIAS}



Figure 8: Transfer Characteristics

13.Detailed Description

The TPD4E1U06 is a quad channel unidirectional TVS ESD protection diode with ultra low capacitance. This device can dissipate ESD strikes above the maximum level specified by the IEC 61000-4-2 international standard. Typical application areas include HDMI, USB2.0, MHL, and DisplayPort. Its 0.8-pF line capacitance makes it suitable for a wide range of applications.

Functional Block Diagram



Figure 9. Circuit Schematic Diagram

Feature Description

IEC 61000-4-2 Level 4 ESD Protection

The I/O pins can withstand ESD events up to ±15-kV contact and air. An ESD/surge clamp diverts the current to ground.

IEC 61000-4-5 Surge Protection

The IO pins can withstand surge events up to 3 A and 45 W (8/20-µs waveform). An ESD-surge clamp diverts this current to ground.

IEC 61000-4-4 EFT Protection

The IO pins can withstand an electrical fast transient burst of up to 80 A (5/50-ns waveform, 4 kV with 50-Ω impedance). An ESD-surge clamp diverts the current to ground.

IO Capacitance

The capacitance between each I/O pin to ground is 0.8 pF.

DC Breakdown Voltage

The DC breakdown voltage of each I/O pin is a minimum of 6.5 V. This ensures that sensitive equipment is protected from surges above the reverse standoff voltage of 5.5 V.

Ultra Low Leakage Current

The I/O pins feature an ultra-low leakage current of 10 nA (Maximum) with a bias of 2.5 V.

Low ESD Clamping Voltage

The I/O pins feature an ESD clamp that is capable of clamping the voltage to 11 V (IPP = 1 A).

Industrial Temperature Range

This device features an industrial operating range of –40°C to +125°C.

14.Typical Application(continued)

Given the USB 2.0 application, the parameters in Table 1 are known.

Table 1. Design Parameters

Parameter	Parameter
Signal range on pins 1, 3, 4, or 6	0 V to 5 V
Operating frequency	240 MHz

Detailed Design Procedure

Signal Range on Pins 1, 3, 4, or 6

The TPD4E1U06 has 4 identical protection channels for signal lines. The symmetry of the device provides flexibility when selecting which of the 4 I/O channels protect which signal lines. Any I/O supports a signal range of 0 to 5.5 V.

Operating Frequency

The TPD4E1U06 has a capacitance of 0.8 pF (typical), supporting USB 2.0 data rates.

Application Curve



Figure 11: Insertion Loss Graph

15.1SOT-23-6 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	b	c	D	E1	E	e	e1	L	θ
Min	1.050	0.000	1.050	0.300	0.100	2.820	1.500	2.650	0.950	1.800	0.300	0°
Max	1.250	0.100	1.150	0.500	0.200	3.020	1.700	2.950	BSC	2.000	0.600	8°

15.2SC70-6 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	b	c	D	E	E1	e	e1	L	L1
Min	0.90	0.00	0.90	0.15	0.08	2.05	2.15	1.15	0.65	1.2	0.26	0.525
Max	1.10	0.10	1.00	0.35	0.15	2.25	2.45	1.35	TYP.	1.4	0.46	REF.

Symbol	θ
Min	0°
Max	8°

16.Ordering information



ww: Batch Code

Order Code	Marking	Package	Base QTY	Delivery Mode
UMW TPD4E1U06DBVR	NG4P	SOT23-6	3000	Tape and reel
UMW TPD4E1U06DCKR	BPS	SC70-6	3000	Tape and reel

17.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.